



Part No:
SPIN

FLOOR SPINNER TOOL

Complete with SS Valve

- Stainless steel vacuum swivel for trouble free service
- Double seal stainless vacuum swivel with 3 bearings on each side
- Low profile - less than 3" tall
- T-style handle for easy control
- All stainless steel construction
- 1 3/4" flow path for maximum flow
- High pressure all stainless steel valve (rated to 140°C, or 285°F)
- Inlet for 2" hose, will also fit 1.5" hose cuff
- Stainless steel angle valve
- Rotating vacuum bypass near handle for ease of use
- Replaceable floor ring allows use of various floor rings and brushes
- Balanced spin jets for high pressure cleaning
- Vacuum slots at the edge to remove water and debris
- High pressure double bearing and ceramic seal assembly
- Splashguard | Nozzle 0502 (2ea) | 2.0" Diameter Tube
- 14" Head Width | 2.75" Head Height | 52" Height

Comes
with
**SPIN
BRUSH**



** Some light cleaning can occur at 500 to 600 PSI. For good cleaning set the pressure at 800 PSI. Best cleaning occurs at 900 to 1100 PSI. Floor damage can occur above 1200 PSI.*

HAND SPINNER TOOL

- Brush attachment to ensure a clean job
- High pressure double bearing and ceramic seal assembly
- Balanced spin jets for high pressure cleaning
- Nozzles angled toward edge of brush for edge cleaning
- Comfortable High pressure handle grip
- 1.5" flow path for maximum flow
- All stainless steel construction | Stainless steel angle valve
- Vacuum slots at the edge to remove water and debris
- Inlet for 1.5" Hose | Splashguard | Nozzle 0502 (2ea) | 1.5" Diameter Tube
- 6" Head Width | 2.75" Head Height | 10" Height



Part No:
HSPIN

** Recommended cleaning at 800 to 1000 PSI. If delicate tile and grout then 500 to 600 PSI.*